



Technical efficiency



sharing our passion

Ecogloss

High-gloss floor finish, highly resistant to traffic

- Innovative formula: increased resistance and greater maintainability
- Skid-resistant (ASTM D2047)
- Prevents the appearance of marks, scratches and clogging
- Without coloring, fragrance-free
- Under the Occupational Exposure Limit (OEL - EU, FR, BE)



Product information:





Ecogloss

High-gloss floor finish, highly resistant to traffic

DESCRIPTION

EcoGloss is an high-gloss floor finish designed for hard and soft floors. Highly-resistant protection from traffic and from hydro-alcoholic gel. EcoGloss is a lasting finish that will provide a clean, luminous and glossy appearance if maintained correctly and regularly.

USE

- Protection: use after stripping with Lino Stripper or Vinyl Stripper, or after applying Granit Sealer. Apply EcoGloss in even, crosslapped coats with a clean mop. For a standardized finish, apply two coats. For maximum cover, apply four coats. Allow sufficient drying time before applying the following coat. Output/liter: 40 to 50m²/layer.
- Regeneration: apply a solution of 10 to 20% with a cleaning cloth on a well cleaned floor, leave to dry and polish until it shines. Don't apply as a cleaning solution. Output: 100m² per liter of product.

DOSAGE

- Protection: ready to use
- Regeneration: 10 to 20%

TECHNICAL CHARACTERISTICS

- Color: milky white
- Pure pH: 8 ± 0,5
- Apply the product preferably at temperatures above 10°C and below 25°C, to avoid irregularities in drying times and the appearance of white marks.
- PolTech EcoGloss is resistant to alcoholic gel.
- The use of this product does not reduce the conductive properties of the floor.
- Anti-skidding according to test ASTM D2047.

STORAGE

Keep the product in its original closed packaging. Protect against freezing temperatures.

ECOLOGICAL INFORMATION

- Biodegradable product (CE 648/2004)
- Packaging 100% recyclable

PACKAGING



Packaging	Reference	EAN code
Carton 2x5 litres	2700258	05411283275828